

CA-755(NTSC)/CA-755P(PAL)

Downloaded from: www.broadcast-trader.com.au

Triax CCU Adaptor for DVW-707/709WS/790WS series and DNW-7/9WS/90/90WS series

- Provides an interface with the Sony Camera Command System so as to achieve the benefits of high-speed, real-time control and instant tactile response
- Furnished with a triax cable interface for use with the CCU-550/700A series Camera Control Unit
- High picture quality
- Direct connection with the camcorder via the camcorder's built-in 40-pin connector
- Long signal transmission capability of up to 600m of \varnothing 8.5mm and 1200m of \varnothing 14.5mm triax cable
- Able to be used with the BVF-55/55CE 5-inch monochrome viewfinder
- Compact and lightweight of 1.9kg (4 lb 3 OZ)

Supplied accessories

| |
|--------------------------------------|
| Operation manual (1) |
| Maintenance manual (1) |
| Cable clamp (1) |
| M3/M4 screws for cable clamp (2 x 2) |

Specification

General

Power consumption: Approx. 13W
Mass: 1.9kg (4 lbs 3 oz)

Input/output connectors

DC IN: XLR-4-pin type, 11.5V to 17V
RET OUT: BNC-type, 1.0Vp-p, 75 Ω
RETURN CONTROL: 6-pin
EARPHONE: MINI-JACK, 8 Ω
CAMERA: 40-pin (DVW-700/700WS series,
DNW-7/9WS/90/90WS series)
CCU: (PAL) Fischer type triax connectors (1)
(NTSC) Kings type triax connectors (1)
INCOM/PGM: Headset XLR-5-pin type

