

KX-2920QM*1 (PAL/NTSC/SECAM/NTSC4.43)

Downloaded from: www.broadcast-trader.com.au

Colour Video Monitor

- 72cm (29-inch) SUPER Trinitron CRT
- Accepts composite, Y/C signals
- Built-in speaker and earphone jack for audio monitoring

Supplied accessories: Remote controller RM-831, Operation manual
Optional accessories: Speakers:SS-X6A
TV tuner unit:TU-1040E

Specifications

Video signal system: CCIR 625 lines, 50 fields/EIA 525 lines, 60 fields
Colour system: PAL/NTSC/SECAM/NTSC4.43*2
Picture tube: 73cm (29-inch). Super Trinitron tube, visible picture size 68cm (27-inch)measured diagonally, 110° deflection
Horizontal resolution: 480 TV lines
Audio power output: 7W+7W, 8 to 16Ω
Power requirements: AC 220 to 240V, 50/60Hz
Power consumption: 109W (typical)
Dimensions: 668(W) × 645(H) × 525(D)mm (26³/₈ × 25¹/₂ × 20³/₄ inches)
Mass: 53 kg(116 lb 13oz)

VIDEO

Line 1 CENELEC 21-pin
Line 2 Loop-through BNC
1Vp-p, sync negative, Automatic 75Ω termination*1
Line 3 (front panel) Composite: Phono
1Vp-p, sync negative, 75Ω
Y/C: Mini DIN 4-pin
Y (luminance): 1Vp-p, sync negative, 75Ω
C (chrominance): PAL: 0.3Vp-p, 75Ω
NTSC: 0.286Vp-p, 75Ω
Line 4 Y/C: Loop-through Mini DIN 4-pin
Y (luminance): 1Vp-p, sync negative, Automatic 75Ωtermination*3
C (chrominance):PAL: 0.3Vp-p, Automatic 75Ω termination*3
NTSC: 0.286Vp-p, Automatic 75Ω termination*3

AUDIO

Line 1 CENELEC 21-pin
Line 2 Loop-through Phono (x2)
-5dBu, high impedance
Line 3 (front panel) Phono
-5dBu, high impedance
Line 4 Loop-through Phono (x2)
-5dBu, high impedance

