

Master Setup Unit

•Successor of MSU-700 •New CPU adopted to realize high-speed digital control •32 scene files capability • Built-in software for the use in HDTV camera system •A single MSU-700A can set up 24 camera/CCU units with 2 CNU-700s and 4 VCS-700s •The unit is connected to CCU or a Camera Command Network Unit (CNU) which is connected to CCU by a special cable of up to 200 m (656 feet) in length and controls the camera functions

Supplied accessories: Operation Manual (1)
Maintenance Manual Part 1 (1)

Specifications

General

Power requirements: 100 to 240 V AC, 50/60 Hz
Current consumption: 0.45 A
Operating temperature: 0°C to 45°C (32°F to 113°F)
Maximum cable length: 200 m (656 feet)
Dimensions (w/h/d): 482 x 222 x 67 mm
(19 x 8 3/4 x 2 3/4 inches)
including projecting parts and controls
Mass: Approx. 4.5 kg (9 lb 15 oz)

Inputs/outputs

REMOTE

CCU/CNU: 8-pin multiconnector (1)
AUX: 8-pin multiconnector (1)
I/O PORT: 50-pin (1)
AC IN: 3-pin (1)

* No fuse or power supply cable is bundled. (MSU-700: They were bundled.)

