

## Video Selector

\*Routes video output of multiple cameras for picture and waveform monitoring \*Accepts up to 6 picture and waveform inputs \*Video output selectable from the MSU-700A/750 or external control equipment through the 37-pin I/O port \*Two picture and waveform outputs available for different system applications

Supplied accessories: AC power cord (1)  
Plug holder for the AC power cord (1)  
4-pin connector (1)  
Operation manual (1)  
Maintenance manual (1)



## Specifications

### General

Power requirements: 100 to 120 VAC, 50/60 Hz (NTSC area)  
220 to 240 VAC, 50/60 Hz (PAL area)  
Power consumption: 0.28 VA  
Operating temperature: 5°C to +45 °C (73°F to +113 °F)  
Mass: Approx. 5.2 kg (11 lb 7 oz)  
Dimensions: Approx. 424(W) x 44(H) x 400(D)mm  
(16 3/4 x 1 3/4 x 15 3/4 inches)

### Input connectors

PIX 1 to PIX 6 input: BNC type (6)  
WF 1 to WF 6 input: BNC type (6)  
1.0 Vp-p(VBS)/0.714 Vp-p(V), 75Ω (NTSC area)  
1.0 Vp-p(VBS)/0.7 Vp-p(V), 75Ω (PAL area)



PIX A input: BNC type (1)  
1.0Vp-p(VBS), 75Ω  
WF A input: BNC type (1)  
1.0Vp-p(VBS), 75Ω  
CHARACTER input: BNC type (1, with loop-through output) 0.7 Vp-p(V),  
75Ω  
AC in: 3-pin

### Output connectors

PIX A and PIX B output: BNC type (1 each), 1.0 Vp-p(VBS), 75Ω  
WF A and WF B output: 1.0 Vp-p(VBS)/0.714 Vp-p(V), 75Ω (NTSC Area)  
1.0 Vp-p(VBS)/0.7 Vp-p(V), 75Ω (PAL Area)  
SYNC output: BNC type (1)  
0.3 Vp-p(VBS), 75Ω, negative polarity  
WF mode: round 4-pin connector (1)

### Remote connectors:

REMOTE: 8-pin multiconnectors (1)  
I/O PORT: D-sub 37-pin(1)